

# VOILE

FLAME RETARDANT SHEER FABRICS

# VOILE



## WHITE



### WHITE

2m 1829290A  
3m 1829290A300  
89mm 1829290D  
127mm 1829290B



### CREAM

2m 1829111A  
89mm 1829111D  
127mm 1829111B



### SANDSHELL

2m 1829642A  
89mm 1829642D  
127mm 1829642B



### MOONDUST

2m 1829593A  
89mm 1829593D  
127mm 1829593B


# ULTRA-FRESH ANTIMICROBIAL

## ROLLER & VERTICAL PLEATED OPTION AVAILABLE

Specifications	Voile
Colour Range	4
Dim Out	Light Filtering
Composition	100% Polyester
Exterior Colour	Self-coloured
Roller Width	2m, 3m - *white only
Roller Roll Length	20m
Vertical Louvre Widths	89mm, 127mm
Vertical Roll Length	100m
Weight	127g/m <sup>2</sup>
Thickness	0.34mm
Blind Types	Roller, Panel, Vertical, Pleated
Colour Fastness (scale of 8)	6-8 - BS EN ISO 105-B02-2014
Flammability Standard	BS 5867 Part 2 Type B
Environmental Certification	OEKO-TEX® STeP Greenshield - VOC Safe Fabrics
Bacteria & Fungal Resistant	ASTM G21, Ultra-Fresh*
Cleaning	Not suitable for cleaning with a damp or wet cloth.

\*Ultra-Fresh is a registered trademark of Microban Products Company

Solar, Optical & Colour Fastness Properties																			
	Solar			Visual			UV Block	CF	DP	SC - EN 14501					Gtot				
	R <sub>s</sub>	A <sub>s</sub>	T <sub>s</sub>	R <sub>v</sub>	A <sub>v</sub>	T <sub>v</sub>				A	B	C	D	E	A	B	C	D	E
Cream	51	6	43	56	2	43	76	7	0	0.54	0.53	0.47	0.31	0.45	0.47	0.46	0.41	0.27	0.40
Moondust	25	46	29	24	49	27	76	8	0	0.70	0.67	0.57	0.33	0.54	0.61	0.59	0.49	0.29	0.47
Sandshell	47	16	36	45	22	32	79	7	0	0.56	0.55	0.48	0.31	0.47	0.49	0.48	0.42	0.27	0.40
White	39	1	60	39	1	60	42	6	0	0.65	0.61	0.52	0.32	0.50	0.56	0.53	0.45	0.28	0.43



**Solar Gain:** The amount of heat increase resulting from solar energy entering a room. It is the total of three separate parts - the amount of energy transmitted directly into the room, the energy which is absorbed by the blind and the proportion of energy which is absorbed by the window.

**R:** % of reflected heat and light.  
**A:** % of absorbed heat and light.  
**T:** % of transmitted heat and light.  
**UV Block:** the % of UV light blocked by the fabric.

**Colour Fastness (CF):** Scale of 8, BS EN ISO 105-B02-2014.  
**Darkening Performance (DP):** Scale of 0-4. 0: lowest opacity 4: highest. A rating of 4 indicates the product is completely opaque with no pinholes or light transfer.

**Shading Co-efficient (SC):** The solar heat gain with the blind at the window divided by the solar heat gain with no blind at the window. The lower the shading co-efficient, the higher the efficiency of the fabric.  
**Gtot:** Amount of heat entering through the glazing and shading combined.

**Glazing system (EN 410)**  
**A:** Clear Single Glazing.  
**B:** Clear Double Glazing.  
**C:** Clear Double Glazing Low Emissivity.  
**D:** Solar Control Double Glazing Low Emissivity.  
**E:** Triple Glazing.

# VOILE

